

15-Watt LED Fixture

The IHT Lighting 15-watt high efficiency LED fixture is designed to provide optimal illumination of agricultural, commercial and industrial facilities. The fixture is designed to provide reliable and consistent performance in a wide variety of lighting applications.

FEATURES

- Suitable for wet/damp locations (4X/IP66)
- 150-degree beam spread (high lumen efficiency design)
- Driver provides consistent output over varying voltage conditions
- Ring Wave Surge Tested (2500volts)
- Lightweight, impact resistant, anti-corrosive enclosure/ lens
- Energy efficient designed to replace 100W incandescent or 25 watt CFL
- Adapter compatibility with most jelly jar junction boxes Easy installation with E26 socket connector accessory
- Low maintenance
- Low operating temperature Aluminum/plastic heat sink

SPECIFICATIONS

Power & Lumen output 15 watt/2100lm (140lm per watt)

Dimensions 4.09 x 4.70 inches (104 x 119.4mm)

Color temperature CCT 5000K (Day White)

Color rendering index 80

Rated life (L80) 5 Years (DOP) / 50,000 Hours

Beam spread 150° Degree

Operating temperature -20°C to +45°C (-4°F to 113°F) Input voltage 100 - 277V/AC 50/60hz

Dimmer type Non - Dimmable

Power factor >0.9

Environment Suitable for wet and damp locations (IP-66)

Thread type M84 x 6 (3.307" OD & .236" pitch) (84mm OD & 6mm pitch)















APPLICATIONS

- Agriculture
- · Commercial / Industrial
- Tunnels
- Warehousing



Included Accessories

JELLY JAR MOUNT

Best for outfitting rooms with existing Jelly Jar Lights

- 15W LED Fixture
- E26 Adapter



JUNCTION BOX MOUNT

Best for outfitting rooms with existing Junction **Boxes**

> Best for new builds

- 15W LED Fixture
- Hardwire Adapter
- Rubber Gasket
- Junction Box adapter with mounting screws



JUNCTION BOX KIT

- 15W LED Fixture Hardwire Adapter
- Rubber Gasket
- Junction Box adapter with mounting screws
- ✓ Junction Box

