

High Bay LED Fixture

P/N: IL-HB-MW-MCCT-120D

Introducing the IHT Lighting High Bay I FD Fixture.

The IHT Lighting High Bay fixture is designed to accommodate a variety of mounting heights and customer applications. The traditional round form factor and ultra-thin design simplify the installation process for contractors. It also provides lighting design flexibility with the option to select from three lumen outputs and three color temperatures.



FEATURES

- 140 lm/watt (Super Bright LED's)
- Water proof and Corrosion proof
- · Excellent light distribution and uniformity
- · Innovative, stylish design
- Heat-sink designed with ADC12 to ensure lifespan up to 50000hrs @L80 25°C
- CCT and Lumen selector
- Up to 28000 Lumen
- · Flicker free
- Available for 120-347V applications
- Built in 0-10V dimming function (down to 6%)
- IP-66 rated

APPLICATIONS

- Agriculture
- Commercial/Industrial
- Tunnels
- Corridors

SPECIFICATIONS

Dimensions

Power & Lumen Output

Dimming Function

Color Temperature CCT

Color Rendering Index

Rated Life (L70)

Housing

Rating

Beam Spread

Operating Temperature

Input Voltage

Power Factor Installation

14.17" x 14.17" x 6.14" (360 x 360 x 156mm)

150/175/200W / 2100/24500/28000lm

0-10V

3500/4000/5000K

Ra83

5 Years (DOP) / 50,000 Hours

Metal Heat sink

IP-66

120°

-22°F to +122°F (-30°C to 50°C)

120-347 V/AC . 50/60hz

>0.9















