

Tri-Proof LED Fixture

The IL-Tek Tri-Proof light is designed for liquid tight, optimal illumination of agricultural, commercial and industrial locations. The entire fixture is designed to meet and exceed **4X** performance standards in a wide variety of lighting applications.



FEATURES

- **110 lm/watt (Super Bright LED's)**
- **Water proof, Dust Proof, Corrosion proof**
- **Innovative, stylish easy clean surface**
- **Light weight, liquid tight modular construction**
- **Super-fast installation, suspended or surface removed**
- **Reliable low voltage series drivers for safe operation**
- **Built in 1-10V dimming function**

APPLICATIONS

- Agriculture
- Commercial/Industrial
- Tunnels
- Corridors
- Warehousing

SPECIFICATIONS

| | |
|--------------------------------------|---|
| Dimensions | 45.25" x 3" x 2.4" (1150 x 76 x 60mm) |
| Power & Lumen Output | 40W / 4400lm |
| Dimming Function | 1-10V |
| Color Temperature CCT | 4000K (Neutral White) |
| Color Rendering Index | >80 |
| Rated Life (L80) | 5 Years (DOP) / 50,000 Hours |
| Housing | High Impact 1 PC Extrusion (Poly-Carbonate) |
| Beam Spread | 110° |
| Operating Temperature | -4°F to +104°F (-20°C to 40°C) Amb |
| Input Voltage | 100-277V/AC |
| Power Factor | >0.95 |
| Working Voltage & Current | 33±2V/DC & 1050mA |
| Net Weight | 3.25lb (1.47kg) |
| Installation | Bracket Mounted Ceiling/Wall |

