



Tri-Proof LED Fixture

IL-TP-4FT-40W-DW-D

IHT Lighting's Tri-Proof LED fixture offers a liquid tight lighting solution for agricultural, commercial, and industrial applications. Our fixtures are designed to meet and exceed 4X performance standards in a wide variety of lighting applications.



- IP-66 rated/ NEMA 4X rated enclosure
- Easy-wiring with removal end cap
- Built-in high-efficiency driver
- 140 lm/watt (Super Bright LED's)
- Innovative, stylish, easy-to-clean surface
- **Excellent light Distribution and uniformity**
- Waterproof, Dust Proof and Corrosion proof
- Built-in 0-10V dimming function (down to 6%)
- Lightweight, modular construction
- Super-fast installation, suspended or surfacemounted w/ brackets

Applications

- Agriculture
- Commercial/Industrial
- Tunnels/Corridors
- Warehousing



















Specifications

Dimensions

Power & Lumen Output

Dimming Function

Color Temperature CCT

Color Rendering Index

Rated Life (L70)

Housing

Rating

Beam Spread

Operating Temperature

Input Voltage

Power Factor

49.53" x 2.78" x 2.62"

40W / 5600lm

0-10V

5000K (Day White)

Ra83

5 Years (DOP) / 50,000 Hours

PC + metalic heat sink

IP-66 & 4X

120°

-4°F to +113°F (-20°C to 45°C)

100-277 V/AC, 50/60hz

>0.9

Contact IHT Group for further information P: 1-800-725-9661 E: lighting@ihtgroup.ca